



**MODEL: TXT SHUTTLE 2+2**  
**TYPE: GASOLINE POWERED PERSONNEL CARRIER**  
**MODEL YEAR: 2006**

## PRODUCT SPECIFICATION

---

**Engine:** ..... 9.0 hp (6.7 kW) rated, 4 cycle, 18 ci (295 cc) twin cylinder, air-cooled, by Robin Subaru  
**Valve Train:**..... Overhead Valve, overhead cam, belt drive  
**Lubrication:** ..... Pressurized oil system, washable permanent filter  
**Balancer:**..... Internal counter rotating balance shaft  
**Ignition:**..... Solid State with crank trigger, electronic timing advance, and RPM limiter  
**Carburetor:** ..... Fixed jet float bowl with remote pulse fuel pump  
**Air Cleaner:**..... Engine mounted integral air intake system with multi-phase silencer and cartridge filter element

**Electrical:** ..... Starter/Generator, solid state regulator, 12 volt maintenance free battery, 430 CCA, 60 minute reserve

**Drive Train:** ..... Automatic, continuously variable transmission (CVT)

**Transaxle:** ..... Differential with helical gears, 13.32:1 ratio, ground speed governor, forward/reverse

**Brakes:** ..... Dual rear wheel mechanical self-adjusting drum brakes. Automatic park brake release with self-compensating system.

**Front Suspension:** ..... Leaf springs with hydraulic shock absorbers

**Rear Suspension:** ..... Leaf springs with hydraulic shock absorbers

**Steering:** ..... Self-compensating single reduction rack and pinion

**Fuel System:** ..... 6.0 gallon (22.8 L) tank

**Speed:** ..... 13 mph  $\pm$  0.5 mph (21 kph  $\pm$  0.8 kph) on level ground

**Weight:** ..... 765 lb (345 kg) dry, fuel capacity 31 lb (14 kg)

**Length:**..... 92.6 in (235 cm)

**Width:**..... 46.5 in (118 cm)

**Height:**..... 48.6 in (123 cm) (at top of steering wheel)

**Ground Clearance:** ..... 4.75 in (12 cm) (at differential)

**Wheel Base:** ..... 65.5 in (166 cm)

**Front Wheel Tread:** ..... 33.5 in (85 cm)

**Rear Wheel Tread:** ..... 38.0 in 97 cm)

**Turning Circle Dia:**..... 18.9 ft (5.72 m)

**Load Capacity:** ..... 800 lb (360 kg) including operator, passengers, accessories, and cargo.

**Body:** ..... Injection molded TPE (Thermoplastic Elastomer)

**Color & Finish:** ..... (Champagne/Hunter Green) Base coat/clear coat finish

**Chassis:** ..... Welded tubular steel with Durashield™ powder coat paint

**Dash Panel:** ..... 4 position drink holders of glass fiber reinforced thermoplastic olefin

**Operator Features:**..... Removable dash mounted key switch, reverse warning indicator, "deadman (operator presence switch)" accelerator control, integral handgrip on hip restraints, manual forward/reverse selector

**Seating:** ..... Vacuum formed fabric backed vinyl covers over cushion foam. Standard seating for operator and three passengers

**Steering Wheel:**..... 13 in (33 cm) with dual handgrips

**OPTIONS/ACCESSORIES:**

Analog Fuel Gauge (In Dash)	<b>S</b>	<b>Convenience:</b>	
High Altitude Jetting	O	4 Bag Attachment	O
		Ash Tray	O
<b>Front Tires:</b>		CE Package	O
Links 18 x 8.50 x 8 (4 Ply Rated)	<b>S</b>	Differential Scuff Guard	O
Sure Trail 18 x 8.50 x 8 (Load Range C)	O	Divot Repair (Sand Bottle, No Side Basket)	O
<b>Rear Tires:</b>		Flip-Flop Kit (Convertible Carrier)	O
Links 18 x 8.50 x 8 (4 Ply Rated)	<b>S</b>	Fold down windshield. Requires Sun Canopy (Top)	O
Sure Trail 18 x 8.50 x 8 (Load Range C)	O	Hour Meter	O
Turf Saver 18 x 8.50 x 8 (4 Ply Rated)	O	Individually Keyed Switch	O
		Locking glove boxes	O
<b>Cosmetic:</b>		Message Holder	O
Non Standard Paint Color	O	Rear Facing Seat	<b>S</b>
Non Standard Seat Color	O	Rear View Mirror. Requires Sun Canopy (Top)	O
Pin Stripes	O	Soft Swipe Spike Cleaner	O
Wheel Covers:		Sun Canopy (Top)	O
6 in (15 cm) Chrome	O	Weather Protection (3 Sided). Requires Sun Canopy (Top)	O
8 in (20 cm) Chrome	O	Windshield. Requires Sun Canopy (Top)	O
Spoke, Black & Gold	O		
Spoke, Black & Silver	O		
<b>Lighting Package:</b>			
Brake Lights	<b>S</b>		
Headlights	<b>S</b>		
Taillights	<b>S</b>		
Turn Signals with 4-Way Flashers	O		

**S** = standard Equipment

**O** = Option or Accessory